

The image as a virtual stage



Computational Photography

Yuxiong Wang, University of Illinois

Slides adopted from Derek Hoiem

Today

- Inserting objects into *legacy* photos
 - Uses single-view geometry and image-based lighting concepts
- Demo for using Blender

Rendering Synthetic Objects into Legacy Photographs

Kevin Karsch

Varsha Hedau

David Forsyth

Derek Hoiem

University of Illinois at Urbana-Champaign
{karsch1,vhedau2,daf,dhoiem}@uiuc.edu




SIGGRAPH ASIA 2011





The polygonal mesh

- Discrete representation of a surface
 - Represented by vertices -> edges -> polygons (faces)



Insert these...



...into this



...into this



Inserting 3D objects into photographs

- Goal: Realistic insertion using a single LDR photo



- Arbitrary lighting environments


- Intuitive, quick and easy to create content

- Home planning/redecoration
- Movies (visual effects)
- Video games



Challenges

- Estimate a physical scene model including:
 - Geometry
 - Surface properties
 - Lighting info
 - Camera parameters



Earlier approaches with scene access



Manual authoring



[Fournier et al. '93]

Earlier approaches with scene access



Manual authoring

Light probe, Inverse GI



[Fournier et al. '93]

[Debevec '98, Yu et al. '99]

Earlier approaches without scene access



Outdoor illumination



[Lalonde et al. '09]

Point source detection



[Wang and Samaras '03,
Lopez-Moreno et al. '10]

System overview


Input image



Object insertion



Scene authoring



Scene synthesis




Overview of getting geometry and lighting



Bounding geometry

Remember Tour into the Picture?
This is also a box model, but camera
doesn't have to face the back wall
- Three vanishing points


Spatial Layout
[Hedau et al. '09]



--- Bounding geometry
■ Supporting geometry
- - -

Spatial Layout
[Hedau et al. '09]

Manual input



Bounding geometry

Supporting geometry

Occluding geometry

Spatial Layout
[Hedau et al. '09]

Spectral
matting [Levin et
al. '09]

Manual input

Manual input

Bounding geometry

Supporting geometry


Occluding geometry


Light sources

Spatial Layout
[Hedau et al. '09]

Spectral
matting [Levin et
al. '09]

Manual input





Area lights

Bounding cuboid

Textured billboard
(with transparency)

Extruded polygon

What the spatial layout provides



Extruded geometry, billboards enable *occlusion*



Box, supporting surfaces enable *object placement*




Box, extruded geometry, lighting enables *shadows*, *inter-reflections*, *caustics*



Camera geometry ensures correct *perspective*





Solving for camera viewpoint

Given 3 orthogonal VPs (at least two finite), can compute projection operator

2D point in homogeneous coordinates

3D point in Cartesian coordinates

$$\lambda p_2 = KRP_3$$

Intrinsic camera matrix

Rotation matrix

Solving for camera viewpoint

Given 3 orthogonal VPs (at least two finite), can compute projection operator: intrinsic matrix

$$K = \begin{bmatrix} f & 0 & u_0 \\ 0 & f & v_0 \\ 0 & 0 & 1 \end{bmatrix} K^{-1} = \begin{bmatrix} 1/f & 0 & -u_0/f \\ 0 & 1/f & -v_0/f \\ 0 & 0 & 1 \end{bmatrix}$$

$$e_i = (1, 0, 0)^T, e_j = (0, 1, 0)^T, e_k = (0, 0, 1)^T$$

$$v_i = KR e_i, v_j = KR e_j, v_k = KR e_k$$

$$(KR)^{-1} v_i = e^i, (KR)^{-1} v_j = e^j, (KR)^{-1} v_k = e^k$$

$$e_i^T e_j = e_j^T e_k = e_i^T e_k = 0$$

$$v_i^T K^{-T} R R^{-1} K^{-1} v_j = v_j^T K^{-T} R R^{-1} K^{-1} v_k = v_i^T K^{-T} R R^{-1} K^{-1} v_k = 0$$

$$v_i^T K^{-T} K^{-1} v_j = v_j^T K^{-T} K^{-1} v_k = v_i^T K^{-T} K^{-1} v_k = 0$$

Solving for camera viewpoint

Given 3 orthogonal VPs (at least two finite), can compute projection operator

$$R = [R_{1c} \quad R_{2c} \quad R_{3c}]$$

$$\lambda v_i = K R e_i \quad e_i = [1, 0, 0]^T$$

$$R_{ic} = \lambda K^{-1} v_i$$

Projecting to image space

Given K , R , and a position in 3D, we can find its corresponding 2D image location:

$$\lambda p_2 = KRP_3$$

What about the reverse?

Given K , R , and a 2D position on the image, what do we know about its 3D location?

What about the reverse?

Given K , R , and a 2D position on the image, what do we know about its 3D location?

$$(KR)^{-1}p_2 = \lambda P_3$$

- Implies a line along which the 3D point lies
- Points on known surfaces can be localized

Modeling occlusions




User-defined boundary




- Tedious/inaccurate
- How can we make this better?

Segmentation with graph cuts



$$Energy(\mathbf{y}; \theta, data) = \sum_i \psi_1(y_i; \theta, data) + \sum_{i,j \in edges} \psi_2(y_i, y_j; \theta, data)$$

Segmentation with graph cuts



$$Energy(\mathbf{y}; \theta, data) = \sum_i \psi_1(y_i; \theta, data) + \sum_{i,j \in edges} \psi_2(y_i, y_j; \theta, data)$$

Refined segmentation



Spectral Matting



Spectral Matting

- Create $N \times N$ matrix describing neighboring pixel similarity (Laplacian matrix, L)
- Extract “smallest” eigenvectors of L
- Soft segmentation defined by linear combination of eigenvectors
 - Scribbles provide constraints to assign to foreground

Spectral Matting



image




spectral components

Spectral matting



Spectral matting




Segmentations as “billboards”



Segmentations as “billboards”



Rendering via ray tracing



Insertion without relighting



...with relighting



Estimating light

- Hypothesize physical light sources in the scene
 - Physical \rightarrow CG representations of light sources found in the real world (area lights, etc)
- Visible sources in image marked by user
 - Refined to best match geometry and materials
- User annotates light shafts; direction vector
 - Shafts automatically matted and refined

Lighting estimation



Lighting estimation




Lighting estimation



Light refinement

Match original image to rendered image



Initial light parameters




Refined light parameters



External light shafts




External light shafts




External light shafts


Shadow matting via Guo et al. [2011]



Setting light shaft direction



External light shafts



Light shaft result



Inserting objects

- Representation of geometry, materials and lights is now compatible with 3D modeling software
- Two methods of insertion/interaction
 - Novice: image space editing
 - Professional: 3D modeling tools (e.g. Maya)
- Scene rendered with physically based renderer (e.g. LuxRender, Blender's Cycles)

Blender demo

Final composite

Additive differential technique [Debevec 1998]

$$\text{composite} = M \cdot R + (1-M) \cdot I + (1-M) \cdot (R-E) \cdot c$$


effect multiplier




I (background)




composite



R (rendered)



E (empty)



M (mask)

Putting it all together

Video: <https://vimeo.com/28962540>

Research directions

- Can we do better with
 - Multiple images?
 - Videos?
 - Depth?
- Better scene understanding?
- How to insert image fragments?

Fully Automated Scene Modeling

Karsch et al. 2014: <http://vimeo.com/101866891>

Summary

- We can accurately predict how a 3D object would look in a depicted scene by recovering
 - Viewpoint: camera matrix, single view geometry
 - Scene geometry: single-view geometry
 - Material: “intrinsic image approaches”
 - Lighting: solve for lights such that rendering reproduces image
- Next classes: interest points, matching and alignment, and stitching